



# ARDEX AF 148

## All Purpose Flooring Adhesive

- Dispersion based
- Low odour and very low emissions
- Extra long open time
- Suitable for installation of vinyl sheets,
- vinyl tiles, LVT and carpet tiles
- Semi-wet and pressure sensitive properties

### DESCRIPTION

ARDEX AF 148 is a single component, dispersion based adhesive for laying LVT, PVC and VCT floorings in sheets, tiles, planks and carpet tiles on internal levelled subfloors

### FEATURES & BENEFITS

- Fast: very fast drying time
- Efficient: extremely fast installation of large areas
- Clean: no risk of soiled floor covering
- Versatile application: useable for trowel and roller application
- Can be used as semi-wet and pressure sensitive
- Ease of application with extra long open time
- Universal: extra long tack for carpet tile installation

### SUBSTRATE PREPARATION

Subfloors must be level, permanently dry, solid and free from cracks, dirt and adhesion-inhibiting substances.

Apply corresponding ARDEX levelling compounds to achieve a levelled floor.

### APPLICATION

Stir ARDEX AF 148 well before using. Apply evenly on the subfloor with a suitable trowel or roller, work from out of the container and avoid adhesive pools. Fit flooring after corresponding airing time of ARDEX AF 148 and press down firmly.

After fitting, roll the complete area again with the roller.

NOTE: The specified processing and drying times refer to +20°C and 50% RH. Differing room climate conditions lead to different times. Do not use ARDEX AF 148 in areas subject to increased moisture, such as entrance areas and wet cells.

### COVERAGE

Depending on the surface structure and absorbability of the subfloor. Approximately 130 - 160g/m<sup>2</sup> with using A1 trowel, on a flat smooth-surface. Coverage may vary if different trowel size is used.

### SAFETY PRECAUTIONS

Product contains isothiazolones. May produce an allergic reaction. Keep out of reach of children Irritant: Avoid eye and skin contact. Use only in well ventilated areas. Keep container tightly closed. In case of contact with eyes and skin, rinse with plenty of water. In event of irritation, seek for medical advice according to the Material Safety Datasheet available upon request and online at [www.ardex.com.tr](http://www.ardex.com.tr).

### DISCLAIMER

The technical datasheets are based on the latest information and given in good faith and represent the best of our knowledge and experience at the time of printing. They are primarily offered for user's consideration and evaluation. It is the responsibility of the user to conduct their own tests to validate the suitability of the products.

It is also the responsibility of the user to ensure that the products are used and handled correctly and in accordance with any applicable standards, the product instructions and recommendations and only for the uses they are intended. As we have no control over site conditions and the execution of the work, we accept no liability for any loss or damage which may rise as a result thereof. We also reserve the right to update the information at any time without prior notice to you to reflect our ongoing research and development.

### TECHNICAL DATA

Raw material base:	Dispersion-based
Airing time:	approx. 5 - 15 min
Working time:	approx. 120 min
Coverage (A1 trowel):	approx. 130 -160 g/m <sup>2</sup>
Cleaning agent:	Water, before the adhesive starts to dry
Packaging:	10 kg plastic pail
Storage time:	ARDEX AF 148 should not be stored in direct contact with sun and protected from freezing. When stored under the correct conditions and unopened, it has a shelf life of 12 months.





# YAPIDAKİ GÖRÜNMEZ GÜÇ