



ARDEX SDB 15

Self Adhesing Waterproofing and Soundproofing Tape

- Flexible and waterproof sealing tape to bridge edges, corners and movement joints
- Used in connection with ARDEX S1-K, ARDEX 8+9, ARDEX 4+5 Flexible Waterproofing Products and ARDEX SK 100 W Sealing Membrane



DESCRIPTION

Stabilized butyl sealing tape reinforced with lamination. The fleece layer allows a good bond with construction chemicals.

For interiors and exteriors, walls and floors.

For sealing and bridging expansion joints, edges, corners, connections at risk of cracking and wall penetrations.

SUBSTRATE PREPARATION

The substrate must be dry, clean, sound, solid and free of releasing agents. Remove all contaminating materials such as dust, oil, paint and curing compounds. Observe instructions and guidelines carefully when used in connection with other ARDEX waterproofing products.

INSTALLATION

Apply the tape adhesive side down, removing half of the protective liner as you go, then remove other half of the liner and firmly press down to ensure full adhesion contact with the substrate. When overlapping between tape runs, the minimum overlap required is 50mm.

To seal floor-wall penetrations, cut a correspondingly large piece from the tape. Cut out an appropriate size opening with a cross-cut. Apply a second layer of tape if required. Afterwards cover the entire tape with ARDEX sealing compounds.

PLEASE NOTE:

ARDEX SDB 15 must not to be used in direct contact with solvent based sealants or adhesives. In case of doubt, create a sample area and make a compatibility test.

Consider the 5cm overlap requirement for coverage calculation

TECHNICAL DATA ACCORDING TO ARDEX QUALITY STANDARDS

Thickness:	0.9 mm
Width:	15 cm
Roll Length:	20 m
Packaging:	Roll in a box
Storage and Shelf Life	Approx. 24 months in a cool and dry place.



YAPIDAKİ GÖRÜNMEZ GÜÇ