Revision: 20.07.2022

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.07.2022

Version number 4 (replaces version 3)

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Product name B11 Härter Hardener 2K Supra A.T. matt
- · Article number: 11483-B11-000
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Hardening agent/ Curing agent
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: LOBA GmbH & Co. KG Leonberger Straße 56 - 62 D-71254 Ditzingen

· 1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

Tel.: +49 (0)7156/357-0

## **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Acute Tox. 4 H332 Harmful if inhaled.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

hexamethylendiisocyanate oligomers, isocyanurate

2-butoxyethyl acetate

cyclohexyldimethylamine

hexamethylene diisocyanate

· Hazard statements

H332 Harmful if inhaled.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

*P103 Read carefully and follow all instructions.* 

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

*P280* Wear protective gloves / eye protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor/x

(Contd. on page 2)

Printing date 20.07.2022 Version number 4 (replaces version 3) Revision: 20.07.2022

### Product name B11 Härter Hardener 2K Supra A.T. matt

(Contd. of page 1)

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH204 Contains isocyanates. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of the substances listed below with harmless additions.

· Dangerous components:		
CAS: 28182-81-2 EC number: 931-274-8 Reg.nr.: 01-2119485796-17	hexamethylendiisocyanate oligomers, isocyanurate  Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	50-100%
CAS: 112-07-2 EINECS: 203-933-3 Index number: 607-038-00-2 Reg.nr.: 01-2119475112-47-xxxx	2-butoxyethyl acetate  Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	5-10%
CAS: 9046-01-9	poly(oxy-1,2-ethanediyl), α-tridecyl-ω-hydroxy-, phosphate Eye Dam. 1, H318;  Skin Irrit. 2, H315; Aquatic Chronic 3, H412	<i>≥1-</i> <2.5%
CAS: 98-94-2 EINECS: 202-715-5 Reg.nr.: 01-2119533030-60	cyclohexyldimethylamine  Flam. Liq. 3, H226; Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; Skin Corr. 1B, H314; Aquatic Chronic 2, H411	≥0.25-<1%
CAS: 822-06-0 EINECS: 212-485-8 Index number: 615-011-00-1 Reg.nr.: 01-2119457571-37- 0000/5/6	hexamethylene diisocyanate  Acute Tox. 1, H330; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5% Skin Sens. 1; H317: C ≥ 0.5 %	<0.1%

<sup>·</sup> Additional information For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

- · After skin contact Instantly wash with water and soap and rinse thoroughly.
- · After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

GB

Printing date 20.07.2022

*Version number 4 (replaces version 3)* 

Product name B11 Härter Hardener 2K Supra A.T. matt

(Contd. of page 2)

Revision: 20.07.2022

## **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents

CO2, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.

- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

## SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class 10
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

## 112-07-2 2-butoxyethyl acetate

WEL Short-term value: 332 mg/m³, 50 ppm Long-term value: 133 mg/m³, 20 ppm

#### 822-06-0 hexamethylene diisocyanate

WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO

(Contd. on page 4)

Printing date 20.07.2022

*Version number 4 (replaces version 3)* 

### Product name B11 Härter Hardener 2K Supra A.T. matt

(Contd. of page 3)

Revision: 20.07.2022

#### · Ingredients with biological limit values:

### 822-06-0 hexamethylene diisocyanate

BMGV 1 µmol creatinine/mol

Medium: urine

Sampling time: At the end of the period od exposure

Parameter: isocyanate-derived diamine

· Additional information: The lists that were valid during the compilation were used as basis.

#### · 8.2 Exposure controls

- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures

Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work.

#### · Breathing equipment:

In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

#### · Hand protection

Protective gloves.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Recommended thickness of the material:  $\geq 0.4$  mm

### Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

*Value for the permeation:* Level  $\leq 6$ 

· Eve/face protection Safety glasses recommended during refilling.

## SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

· Smell: Characteristic Not determined. · Odour threshold: Not determined · Melting point/freezing point:

· Boiling point or initial boiling point and boiling

range Not determined · Flammability *Not applicable.* Not determined. · Lower: · Upper: Not determined.

65 °C (111109-77-4 1-methoxy-3-(3-methoxypropoxy)-· Flash point:

propane)

· Decomposition temperature: Not determined. Not determined.  $\cdot pH$ 

(Contd. on page 5)

(Contd. of page 4)

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.07.2022 Version number 4 (replaces version 3) Revision: 20.07.2022

#### Product name B11 Härter Hardener 2K Supra A.T. matt

· Viscosity: 18 s (DIN 53211/4) · Kinematic viscosity at 20 °C · dvnamic: Not determined. · Solubility Not miscible or difficult to mix · Water: Partition coefficient n-octanol/water (log value) Not determined. · Steam pressure: Not determined. Density and/or relative density · Density at 20 °C  $1.07 \, \text{g/cm}^3$ Not determined. · Relative density · Vapour density Not determined. · 9.2 Other information · Appearance: Fluid · Form: · Important information on protection of health and environment, and on safety. · Self-inflammability: Product is not selfigniting. · Explosive properties: Product is not explosive. · Solids content: 69.0 % · Change in condition · Evaporation rate Not determined.

· Information with regard to physical hazard classes · Explosives Void

· Flammable gases Void · Aerosols Void · Oxidising gases Void · Gases under pressure Void · Flammable liquids Void · Flammable solids Void Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable Void gases in contact with water

gases in contact with water Vola
Oxidising liquids Void
Oxidising solids Void
Organic peroxides Void
Corrosive to metals Void
Desensitised explosives Void

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions

Reacts with alcohols, amines, aqueous acids and alkalis

Reacts with water

Danger of bursting

- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

Printing date 20.07.2022

Version number 4 (replaces version 3)

Product name B11 Härter Hardener 2K Supra A.T. matt

(Contd. of page 5)

Revision: 20.07.2022

## **SECTION 11: Toxicological information**

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if inhaled.

· LD/LC50	values that	are relevant for classification:
28182-81	2 hexameti	hylendiisocyanate oligomers, isocyanurate
Oral	LD50	>2,500 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rat)
112-07-2 2	-butoxyeth	ıyl acetate
Oral	LD50	2,400 mg/kg (rat)
Dermal	LD50	1,580 mg/kg (rabbit)
9046-01-9	poly(oxy-1	,2-ethanediyl), α-tridecyl-ω-hydroxy-, phosphate
Dermal	LD50	>2,000 mg/kg (kan)
98-94-2 cy	clohexyldi	methylamine
Oral	LD50	272 mg/kg (rat)
Dermal	LD50	370 mg/kg (rat)
Inhalative	LC50/4 h	4.45 mg/l (rat)
822-06-0 h	examethyl	lene diisocyanate
Oral	LD50	959 mg/kg (rat)
Dermal	LD50	>7,000 mg/kg (rat)
Inhalative		0.124 mg/l (rat)

- · Serious eye damage/irritation Causes serious eye irritation.
- · Respiratory or skin sensitisation May cause an allergic skin reaction.
- · STOT-single exposure May cause respiratory irritation.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

### 9046-01-9 poly(oxy-1,2-ethanediyl), α-tridecyl-ω-hydroxy-, phosphate

EC50/48 h 10 mg/L (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water.

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

(Contd. on page 7)

Printing date 20.07.2022 Version number 4 (replaces version 3)

Product name B11 Härter Hardener 2K Supra A.T. matt

(Contd. of page 6)

Revision: 20.07.2022

Harmful to aquatic organisms

## **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN number or ID number	17 . 1	
ADR, IMDG, IATA	Void	
14.2 UN proper shipping name		
ADR, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR, IMDG, IATA	Void	
14.5 Environmental hazards:	Not applicable.	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according	g to IMO	
instruments	Not applicable.	
UN "Model Regulation":	Void	

## SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations
- · Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Alteration in the context will be marked with a cross (\*).

· Relevant phrases

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

(Contd. on page 8)

Revision: 20.07.2022

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 20.07.2022

Version number 4 (replaces version 3)

### Product name B11 Härter Hardener 2K Supra A.T. matt

\* \* Data compared to the previous version altered.

(Contd. of page 7) H311 Toxic in contact with skin. H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H330 Fatal if inhaled. Toxic if inhaled. H331 H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation. H335 H411 Toxic to aquatic life with long lasting effects. H412 Harmful to aquatic life with long lasting effects. EUH204 Contains isocyanates. May produce an allergic reaction. · Department issuing data specification sheet: Productmanagement. · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids - Category 3 Acute Tox. 3: Acute toxicity - Category 3 Acute Tox. 1: Acute toxicity - Category 1 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

GB