
icconting to 1907/2000/EC, Article

Printing date 08.05.2023

Version number 3 (replaces version 2)

Revision: 08.05.2023



Printing date 08.05.2023

Version number 3 (replaces version 2)

Revision: 08.05.2023

Product name B19 Härter Hardener 2K FactoryStyle

	(Contd. of page 1)
· Hazard stat	ements
H332 Harm	ful if inhaled.
H315 Cause	es skin irritation.
H318 Cause	es serious eye damage.
H317 May 6	cause an allergic skin reaction.
H335 May 6	cause respiratory irritation.
Precaution	ary statements
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280	Wear protective gloves / eye protection.
P305+P351	+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
· 2.3 Other h	azards
. Regults of 1	DRT and NPNR assassment

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of the substances listed below with harmless additions.

· Dangerous components:		
CAS: 28182-81-2 EC number: 931-274-8 Reg.nr.: 01-2119485796-17	hexamethylendiisocyanate oligomers, isocyanurate Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335	50-100%
CAS: 9046-01-9	poly(oxy-1,2-ethanediyl), α-tridecyl-ω-hydroxy-, phosphate Eye Dam. 1, H318; Skin Irrit. 2, H315; Aquatic Chronic 3, H412	≥3-<5%
CAS: 98-94-2 EINECS: 202-715-5 Reg.nr.: 01-2119533030-60	cyclohexyldimethylamine	<i>≤</i> 1%
CAS: 822-06-0 EINECS: 212-485-8 Index number: 615-011-00-1 Reg.nr.: 01-2119457571-37- 0000/5/6	hexamethylene diisocyanate Acute Tox. 1, H330; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: $C \ge 0.5$ % Skin Sens. 1; H317: $C \ge 0.5$ %	<0.1%

· Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• 4.1 Description of first aid measures

• After inhalation

Supply fresh air and call for doctor for safety reasons.

In case of unconsciousness bring patient into stable side position for transport.

• After skin contact Instantly wash with water and soap and rinse thoroughly.

• After eye contact Rinse opened eye for several minutes under running water.

• After swallowing In case of persistent symptoms consult doctor.

• 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.05.2023

Version number 3 (replaces version 2)

Revision: 08.05.2023

(Contd. of page 2)

Product name B19 Härter Hardener 2K FactoryStyle

• **4.3 Indication of any immediate medical attention and special treatment needed** No further relevant information available.

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents Use fire fighting measures that suit the environment.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

• 6.1 Personal precautions, protective equipment and emergency procedures Not required.

6.2 Environmental precautions: Do not allow product to reach sewage system or water bodies. Inform respective authorities in case product reaches water or sewage system.
6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Ensure adequate ventilation.

• 6.4 Reference to other sections See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling
- Keep containers tightly sealed.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage

• Requirements to be met by storerooms and containers: No special requirements.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: None.
- · Storage class 10
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1	Control	parameters
--------------	---------	------------

· Components with critical values that require monitoring at the workplace:

822-06-0 hexamethylene diisocyanate

- WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³
 - Sen; as -NCO

· Ingredients with biological limit values:

822-06-0 hexamethylene diisocyanate

BMGV 1 µmol creatinine/mol Medium: urine Sampling time: At the end of the period od exposure Parameter: isocyanate-derived diamine

(Contd. on page 4)

- GB

Printing date 08.05.2023

*

Version number 3 (replaces version 2)

Revision: 08.05.2023

Product name B19 Härter Hardener 2K FactoryStyle

	(Contd. of page
Additional information: The lists that were valid during the compilation were used as basis.	
8.2 Exposure controls	
Appropriate engineering controls No further data; see section 7.	
Individual protection measures, such as personal protective equipment	
General protective and hygienic measures	
Instantly remove any soiled and impregnated garments.	
Wash hands during breaks and at the end of the work.	
Breathing equipment:	
In case of brief exposure or low pollution use breathing filter apparatus. In case of inter	nsive or long
exposure use breathing apparatus that is independent of circulating air.	_
Hand protection	
Protective gloves.	
The glove material has to be impermeable and resistant to the product/ the substance/ the prep	paration.
Selection of the glove material on consideration of the penetration times, rates of dig	ffusion and the
degradation	-
Material of gloves	
Nitrile rubber, NBR	
The selection of the suitable gloves does not only depend on the material, but also on further i	
and varies from manufacturer to manufacturer. As the product is a preparation of several	
resistance of the glove material can not be calculated in advance and has therefore to be chec	cked prior to t
application.	
Recommended thickness of the material: ≥ 0.4 mm	
Penetration time of glove material	
The exact break trough time has to be found out by the manufacturer of the protective glove	es and has to
observed.	
For the mixture of chemicals mentioned below the penetration time has to be at lea	st 480 minut
(Permeation according to EN 374 Part 3: Level 6).	
Value for the permeation: Level ≤ 6	
Eye/face protection Safety glasses recommended during refilling.	
SECTION 9: Physical and chemical properties	
9.1 Information on basic physical and chemical properties	

General Information	-
Physical state	Fluid
Colour:	Colourless
Smell:	Odourless
Odour threshold:	Not determined.
Melting point/freezing point:	Not determined
Boiling point or initial boiling point and boiling	
range	150 °C
Flammability	Not applicable.
Lower:	Not determined.
Upper:	Not determined.
Flash point:	160 °C
Decomposition temperature:	Not determined.
pH at 20 °C	7
Viscosity:	
Kinematic viscosity	Not determined.
Kinematic viscosity	
dynamic at 20 °C:	1,500 mPas
Solubility	
Water:	Not miscible or difficult to mix
Partition coefficient n-octanol/water (log value)	9
Steam pressure at 20 °C:	0.00002 hPa

(Contd. on page 5)

GB

22 Vancian number 2 (n

Printing date 08.05.2023

Version number 3 (replaces version 2)

Revision: 08.05.2023

Product name B19 Härter Hardener 2K FactoryStyle

		(Contd. of page
Vapour pressure:		
Density and/or relative density		
Density at 20 °C	1.13 g/cm^3	
Relative density	Not determined.	
Vapour density	Not determined.	
9.2 Other information		
Appearance:		
Form:	Fluid	
Important information on protection of heal environment, and on safety.	th and	
Self-inflammability:	Product is not selfigniting.	
Explosive properties:	Product is not explosive.	
Change in condition	1	
Evaporation rate	Not determined.	
Information with regard to physical hazard o	classes	
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions Reacts with alcohols, amines, aqueous acids and alkalis Reacts with water

Danger of bursting

- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Harmful if inhaled.
- · LD/LC50 values that are relevant for classification:

28182-81-2 hexamethylendiisocyanate oligomers, isocyanurate

Oral LD50 >2,500 mg/kg (rat)

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 08.05.2023

Version number 3 (replaces version 2)

Revision: 08.05.2023

Product name B19 Härter Hardener 2K FactoryStyle

		(Contd. of page 5)
Dermal	LD50	>2,000 mg/kg (rat)
9046-01-9	poly(oxy-	l,2-ethanediyl), α-tridecyl-ω-hydroxy-, phosphate
Dermal	LD50	>2,000 mg/kg (kan)
98-94-2 су	clohexyldi	methylamine
Oral	LD50	272 mg/kg (rat)
Dermal	LD50	370 mg/kg (rat)
Inhalative	LC50/4 h	4.45 mg/l (rat)
822-06-0 h	examethy	lene diisocyanate
Oral	LD50	959 mg/kg (rat)
Dermal	LD50	>7,000 mg/kg (rat)
Inhalative	LC50/4 h	0.124 mg/l (rat)
· Skin corro	sion/irrita	tion Causes skin irritation.

• Serious eye damage/irritation Causes serious eye damage.

• *Respiratory or skin sensitisation* May cause an allergic skin reaction.

· STOT-single exposure May cause respiratory irritation.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

9046-01-9 poly(oxy-1,2-ethanediyl), α-tridecyl-ω-hydroxy-, phosphate

EC50/48 h 10 mg/L (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.

· 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

· 12.7 Other adverse effects

- Remark: Harmful to fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water. Do not allow product to reach ground water, water bodies or sewage system. Danger to drinking water if even small quantities leak into soil. Harmful to aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.

(Contd. on page 7)

Printing date 08.05.2023

Version number 3 (replaces version 2)

Revision: 08.05.2023

(Contd. of page 6)

Product name B19 Härter Hardener 2K FactoryStyle

· Uncleaned packagings:

• *Recommendation: Disposal must be made according to official regulations.*

SECTION 14: Transport informat	ion	
14.1 UN number or ID number ADR, IMDG, IATA	Void	
14.2 UN proper shipping name ADR IMDG, IATA	Void 1263 FARBZUBEHÖRSTOFFE Void	
14.3 Transport hazard class(es)	, 014	
ADR, ADN, IMDG, IATA Class	Void	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Maritime transport in bulk according instruments	g to IMO Not applicable.	
UN "Model Regulation":	Void	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· National regulations

· Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Alteration in the context will be marked with a cross (*).

· Relevant phrases

- H226 Flammable liquid and vapour.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.

(Contd. on page 8)

GB

Printing date 08.05.2023

Version number 3 (replaces version 2)

Revision: 08.05.2023

Product name B19 Härter Hardener 2K FactoryStyle

	(Contd. of page 7)
H331	Toxic if inhaled.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H411	Toxic to aquatic life with long lasting effects.
H412	
	Harmful to aquatic life with long lasting effects.
	4 Contains isocyanates. May produce an allergic reaction.
	ication according to Regulation (EC) No 1272/2008
	ssification of the mixture is generally based on the calculation method using substance data according clation (EC) No 1272/2008.
Depart	ment issuing data specification sheet: Product safety
Abbrev	iations and acronyms:
ADR: Ac	cord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the
	onal Carriage of Dangerous Goods by Road)
	nternational Maritime Code for Dangerous Goods
	ernational Air Transport Association
	obally Harmonised System of Classification and Labelling of Chemicals
EINECS:	European Inventory of Existing Commercial Chemical Substances
	European List of Notified Chemical Substances
	emical Abstracts Service (division of the American Chemical Society)
	thal concentration, 50 percent othal dose, 50 percent
	sistent, Bioaccumulative and Toxic
	ry Persistent and very Bioaccumulative
	1. 3: Flammable liquids – Category 3
	x. 3: Acute toxicity – Category 3
	x. 1: Acute toxicity – Category 1
	x. 4: Acute toxicity – Category 4
	r. 1B: Skin corrosion/irritation – Category 1B
	. 2: Skin corrosion/irritation – Category 2
Eye Dam	. 1: Serious eye damage/eye irritation – Category 1
	2: Serious eye damage/eye irritation – Category 2
	is. 1: Respiratory sensitisation – Category I
	: 1: Skin sensitisation – Category 1
	3: Specific target organ toxicity (single exposure) – Category 3
	Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
	Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
* Data	compared to the previous version altered.