



**DECLARATION OF PERFORMANCE**  
**in accordance with Annex III of Regulation (EU) No 305/2011**  
**(Construction Product Regulation)**  
**amended by Commission Delegated Regulation (EU) No 574/2014**

for the product **ARDEX X 7 G Microtec**  
**No 40001**

1. Unique identification code of the product type: **EN 12004:C2TE-S1**
2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

**Cementitious Adhesive**

3. Name, registered trade name or registered trade mark and contact address of the manufacturer:

**ARDEX Yapi Malzemeleri Ltd. Sti.**  
**Istanbul Deri Organize Sanayi Bölgesi**  
**Desen Sokak No: 14/A C-1 Özel Parsel**  
**34956 Tuzla/Istanbul**  
**TURKEY**

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2) of the Regulation (EU) no 305/2011:

**not relevant**

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3**

- 6a. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body **TURKISH STANDARDS INSTITUTION (TSE)** with the identification number **1783** performed the test according to EN 12004:2007 and according to EN 12002.

- 6b. In case of the declaration of performance concerning a construction product for which a European Technical Assessment was issued:

**Not relevant**

7. Declared Performance:

Essential Characteristics	Performance	Harmonised Technical Specification
Initial tensile adhesion strength:	≥ 1.0 N/mm <sup>2</sup>	EN 12004:2007+A1
Tensile adhesion strength after water immersion:	≥ 1.0 N/mm <sup>2</sup>	EN 12004:2007+A1
Tensile adhesion strength after heat ageing:	≥ 1.0 N/mm <sup>2</sup>	EN 12004:2007+A1
Tensile adhesion strength after freeze-thaw cycles:	≥ 1.0 N/mm <sup>2</sup>	EN 12004:2007+A1
Fire class:	E	EN 12004:2007+A1
Release of dangerous substances:	see material safety data sheet	-

Additional Characteristics	Performance	Harmonised Technical Specification
Open time:	≥ 0.5 N/mm <sup>2</sup> after not less than 30 minutes	EN 12004:2007+A1
Slip:	≤ 0.5 mm	EN 12004:2007+A1
Transverse deformation:	≥ 2.5 mm and < 5 mm	EN 12004:2007+A1

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

**ARDEX GmbH**  
Friedrich-Ebert-Str. 45  
58453 Witten

---

Dr. Jörg W. Sieksmeier  
R & D Director

Bernd Unterbrink  
R & D Section Head

Witten, 9<sup>th</sup> November 2018

(Place and date of issue)