



# ARDEX TP 50

## Edge Insulation Strip

- Tolerates the internal stress between building elements
- Provides sounded-deadening between screeds, levelling compounds, tiles, natural stones etc. on floors and walls.
- Provides ventilation of the back side and prevents sound bridge formation in wooden constructions
- Prevents sound bridge formation and used as decoupling tape on walls in touch with unbonded floor coverings.
- Easy and comfortable application
- Self Adhesive



### DESCRIPTION

ARDEX TP 50 is a polyethylene foam based self-adhesive soft tape that can be used for the following purposes on floors.

Prevents transfer of stress from structural elements of the bulding to screed, levelling compounds and similair coverings applied on the floor.

Provides sounded-deadening between screeds, levelling compounds, tiles, natural stones etc. on floors and walls.

Provides ventilation of the back side and prevents sound bridge formation in wooden constructions

Prevents sound bridge formation and used as decoupling tape on walls in touch with unbonded floor coverings.

Can be used both in interiors and exteriors.

### SUBSTRATE PREPARATION

The substrate must be dry, clean, sound, solid and free of releasing agents. Remove all contaminating materials such as dust, oil, paint and curing compounds.

### APPLICATION

Apply the tape adhesive side down, removing the protective liner as you go and firmly press down to ensure full adhesion contact with the substrate.

At corner spots, adapt the tape to the substrate or apply in two sepe- rate parts and cover their junction with an additional strip.

### NOTE

After applying the relevant screed or self-leveling compound, the expo- sed parts of the insulating tape can be easily cut with a utility knife.

The excess parts of the strip should be removed after applying the ce- ramic, natural stone and other tile coverings, prior to their grouting.

### TECHNICAL DATA ACCORDING TO ARDEX QUALITY STANDARDS

Width:	approx. 5 cm
Thickness:	approx. 5 mm
Water vapor permeability:	Yes
Resistance to moisture:	Yes
Color:	Gray
GHS/CLP classification:	None
GGVSEV/ADR classification:	None
Packaging:	Box consisting of 4 rolls, 25m each
Storage and Shelf Life:	Approx. 12 months in a cool and dry place.



# YAPIDAKİ GÖRÜNMEZ GÜÇ