

DECLARATION OF PERFORMANCE in accordance with Annex III of Regulation (EU) No 305/2011 (Construction Product Regulation) amended by Commission Delegated Regulation (EU) No 574/2014

for the product ARDEX V 2001 T No 40030

- 1. Unique identification code of the product type: EN 998-1: GP-CS IV-Wc1
- 2. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

General purpose mortar (GP) for internal and external use

3. Name, registered trade name or registered trade mark and contact address of the manufacturer:

ARDEX Yapi Malzemeleri Ltd. Sti. Istanbul Deri Organize Sanayi Bölgesi Desen Sokak No: 14/A C-1 Özel Parsel 34956 Tuzla/Istanbul TURKEY

4. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2) of the Regulation (EU) No 305/2011:

Not relevant

5. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4 System 3 for reaction to fire

- 6a. In case of the declaration of performance concerning a construction product covered by a harmonised standard:
 - The notified body **ERA LABORATUVARLARI A.Ş.** with the identification number **2184** performed the reaction to fire.
- 6b. In case of the declaration of performance concerning a construction product for which a European Technical Assessment was issued:

Not relevant

7. Declared Performance:

Essential Characteristics	Performance	Harmonised Technical Specification
Reaction to fire:	A1	EN 998-1:2016
Water absorption:	W _c 1	EN 998-1:2016
Water permeability after weathering cycles:	NPD	EN 998-1:2016
Water vapour diffusion:	≤ 25	EN 998-1:2016
Adhesion:	≥ 1.0 N/mm², fracture pattern B	EN 998-1:2016
Adhesion after weathering cycles:	NPD	EN 998-1:2016
Thermal conductivity/Density:	0.60 W/(m*K) (P = 50 %)	EN 998-1:2016
Thermal conductivity (for heat insulating mortar):	NPD	EN 998-1:2016
Durability of OC mortar:	NPD	EN 998-1:2016
Durability of all mortars except OC:	Evaluation based on provisions valid in the intended place of use of the mortar	EN 998-1:2016
Dangerous substances:	See safety data sheet	EN 998-1:2016

8. The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

ARDEX GmbH

Dr. Jörg W. Sieksmeier

FO 150 hard

Bernd Unterbrink

R & D Director

Witten, 9th September 2021

(Place and date of issue)