



ARDEX E 25

Mortar Admix for ARDEX Smoothing Compounds

- An ideal blend product for enhancing cementitious mortar and leveling screeds.
- Boosts elasticity and wear resistance.
- Facilitates easy application.



Areas of Application

Used as an additive with ARDEX floor powder products to strengthen cementitious mortar, leveling, and repair screeds, and self-leveling thin screeds.

Enhances the surface hardness, wear resistance, and elasticity of cementitious screeds while reducing the risk of cracking.

Suitable for indoor use.

Product Composition

Water-based white synthetic resin dispersion, free of solvents.

Application

A clean container should be used to mix the product with the powder.

ARDEX E 25 is mixed with water at a ratio of 1:2.5 to 1:5 to prepare the mixing water for the mortar. Then, by adding coarse powder, it is mixed with an electric mixer until the desired consistency is achieved.

Product Consumption and Requirement

Consumption may vary depending on the mixing water values of the powder product and the desired consistency of the mortar. Generally, ARDEX E 25 is added to the mixing water at a rate of 1–2.5 kg per 25 kg of powder, depending on the situation.

In case of discrepancies, it is recommended to conduct a sample application.

Safety Information

GISCODE D1 = Does not contain solvents.

Product contents: 5-Chloro-2-methylisothiazolin-3-one and 2-methylisothiazolin-3-one (3:1).

May cause allergic reactions.

Should be kept out of reach of children.

Its content and packaging should be disposed of according to local, national, and international regulations.

GHS/CLP Classification: None

GGVSEB/ADR Classification: None

Packaging: 5kg and 25kg drums

Storage and Shelf Life: It can be stored for approximately 12 months in its original unopened packaging, in a cool but frost-protected, sun-free environment.

The information provided in this document is based on current scientific and practical data and may vary depending on site conditions and use of product. ARDEX is only obliged to ensure the quality of the product at the foreseen standard conditions. ARDEX does not authorize anyone, including ARDEX Representatives, to make any statements which supersede, modify or supplement the information provided on its printed literature or package labels without written confirmation from the Ardex Technical Service Department. This document is valid until future revisions.