Revision: 01.06.2022

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2022

Version number 9 (replaces version 8)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Product name 2K Supra A.T.

· Article number: 11465-000

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Dispersion paint/ Latex paint

Multi-pack product

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier: LOBA GmbH & Co. KG Leonberger Straße 56 - 62

D-71254 Ditzingen

Tel.: +49 (0)7156/357-0

· Informing department: service@loba.de

· 1.4 Emergency telephone number:

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the GB CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of the substances listed below with harmless additions.

- Dangerous components: CAS: 34590-94-8 EINECS: 252-104-2 Reg.nr.: 01-211-945-0011-60-xxxx	Dipropylene glycol monomethyl ether substance with a Community workplace exposure limit	2.5-5%
CAS: 111-76-2 EINECS: 203-905-0 Index number: 603-014-00-0 Reg.nr.: 01-2119475108-36-xxxx	2-butoxyethanol • Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg	<2.5%

(Contd. on page 2)

Revision: 01.06.2022

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2022

Version number 9 (replaces version 8)

Product name 2K Supra A.T.

		(Contd. of page 1)
CAS: 78-93-3	butanone	<0.5%
EINECS: 201-159-0	🚸 Flam. Liq. 2, H225; 🕠 Eye Irrit. 2, H319;	
Index number: 606-002-00-3	STOT SE 3, H336, EUH066	
Reg.nr.: 01-2119457290-43-xxxx		
CAS: 55965-84-9	reaction mass of: 5-chloro-2-methyl-4-	≥0.00025-<0.0015%
EC number: 911-418-6	isothiazolin-3-one [EC no. 247-500-7] and 2-	
Index number: 613-167-00-5	methyl-2H-isothiazol-3-one [EC no. 220-239-6]	
Reg.nr.: 01-2120764691-48	(3:1)	
	Acute Tox. 3, H301; Acute Tox. 2, H310;	
	Acute Tox. 2, H330; 📀 Skin Corr. 1C, H314; Eye	
	Dam. 1, H318; 🕸 Aquatic Acute 1, H400	
	(M=100); Aquatic Chronic 1, H410 $(M=100)$;	
	♦ Skin Sens. 1A, H317	
	Specific concentration limits:	
	Skin Corr. 1C;H314: C ≥ 0.6 %	
	Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 %	
	Eye Dam. 1; H318: C ≥ 0.6 %	
	Eye Irrit. 2; H319: $0.06 \% \le C < 0.6 \%$	
	Skin Sens. 1A; H317: C ≥ 0.0015 %	
· Additional information For the wo	rding of the listed hazard phrases refer to section 10	б.

SECTION 4: First aid measures

- 4.1 Description of first aid measures
- · After inhalation Supply fresh air; consult doctor in case of symptoms.
- · After skin contact The product is not skin irritating.
- · After eye contact Rinse opened eye for several minutes under running water.
- · After swallowing In case of persistent symptoms consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents Use fire fighting measures that suit the environment.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Do not allow product to reach sewage system or water bodies.

Inform respective authorities in case product reaches water or sewage system.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

No dangerous materials are released.

See Section 7 for information on safe handling

See Section 8 for information on personal protection equipment.

See Section 13 for information on disposal.

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2022

Version number 9 (replaces version 8)

Product name 2K Supra A.T.

(Contd. of page 2)

Revision: 01.06.2022

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions necessary if used correctly.
- Information about protection against explosions and fires: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- ·Storage
- Requirements to be met by storerooms and containers: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Storage class 12
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Components with critical values that require monitoring at the workplace:

34590-94-8 Dipropylene glycol monomethyl ether

WEL Long-term value: 308 mg/m³, 50 ppm

111-76-2 2-butoxyethanol

WEL Short-term value: 246 mg/m³, 50 ppm

Long-term value: 123 mg/m³, 25 ppm

Sk, BMGV

78-93-3 butanone

WEL Short-term value: 899 mg/m³, 300 ppm

Long-term value: 600 mg/m³, 200 ppm

Sk, BMGV

Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BMGV 240 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: butoxyacetic acid

78-93-3 butanone

BMGV 70 umol/L

Medium: urine

Sampling time: post shift

Parameter: butan-2-one

- · Additional information: The lists that were valid during the compilation were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures Wash hands during breaks and at the end of the work.
- · Breathing equipment: Not required.
- · Hand protection

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

Nitrile rubber, NBR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 4)

(Contd. of page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Version number 9 (replaces version 8) Printing date 01.06.2022 Revision: 01.06.2022

Product name 2K Supra A.T.

Recommended thickness of the material: ≥ 0.4 mm

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).

Value for the permeation: Level \leq 6

· Eye/face protection Safety glasses recommended during refilling.

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

· Colour: According to product specification

· Smell: Recognisable Not determined. · Odour threshold: Not determined Melting point/freezing point:

· Boiling point or initial boiling point and boiling

100 °C range · Flammability Not applicable.

· Lower: Not determined. · Upper: Not determined. · Flash point: *Not applicable* · Decomposition temperature: Not determined. Not determined. $\cdot pH$

· Viscosity:

· Kinematic viscosity at 20 °C 17 s (ISO 4 mm) · dynamic: Not determined.

·Solubility

· Water: Not miscible or difficult to mix

Not determined. · Partition coefficient n-octanol/water (log value) · Steam pressure: Not determined.

Density and/or relative density

· Density at 20 °C 1.05 g/cm^3 Not determined. · Relative density · Vapour density Not determined.

· 9.2 Other information

· Appearance:

Fluid · Form:

· Important information on protection of health and

environment, and on safety.

· Self-inflammability: Product is not selfigniting. Product is not explosive. · Explosive properties:

· Change in condition

Not determined. · Evaporation rate

Information with regard to physical hazard classes

Void· Explosives · Flammable gases Void Void · Aerosols Void · Oxidising gases Void · Gases under pressure · Flammable liquids Void Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids

(Contd. on page 5)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2022

Version number 9 (replaces version 8)

Product name 2K Supra A.T.

(Contd. of page 4)

Revision: 01.06.2022

· Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable Void gases in contact with water · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void · Desensitised explosives Void

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

· LD/LC50 1	values that o	are relevant for classification:
34590-94-	8 Dipropyle	ne glycol monomethyl ether
Oral	LD50	5,135 mg/kg (rat)
Dermal	LD50	9,500 mg/kg (rat)
111-76-2 2	-butoxyeth	anol
Oral	LD50	1,200 mg/kg (ATE)
		1,480 mg/kg (rat)
Inhalative	LC50/4 h	450 mg/l (rat)
78-93-3 bu	tanone	
Oral	LD50	3,300 mg/kg (rat)
Dermal	LD50	5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	12,000 mg/l (rat)
55965-84-		nass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-azol-3-one [EC no. 220-239-6] (3:1)
Oral	LD50	457 mg/kg (rat)
Dermal	LD50	660 mg/kg (rat)
Inhalative	LC50/4 h	0.33 mg/l (rat)
		0.188 mg/L (fish)

· 11.2 Information on other hazards

· Endocrii	ne disrupting properties	
78-93-3	butanone	List II

- GI

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2022

Version number 9 (replaces version 8)

Product name 2K Supra A.T.

(Contd. of page 5)

Revision: 01.06.2022

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)

EC50/48 h 0.1 mg/L (daphnia)
EC50/72 h 0.027 mg/L (Algae)
NOEC 0.0012 mg/L (Algae)
0.004 mg/L (daphnia)
0.098 mg/L (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system. After prior treatment product has to be landfilled or incinerated under adherence to the regulations pertaining to the disposal of especially hazardous waste.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

· 14.1 UN number or ID number		
· ADR, ADN, IMDG, IATA	Void	
· 14.2 UN proper shipping name		
· ADR, ADN, IMDG, IATA	Void	
· 14.3 Transport hazard class(es)		
· ADR, ADN, IMDG, IATA		
· Class	Void	
· 14.4 Packing group		
· ADR, IMDG, IATA	Void	
· 14.5 Environmental hazards:		
· Marine pollutant:	No	

-GB

Revision: 01.06.2022

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2022

Version number 9 (replaces version 8)

Product name 2K Supra A.T.

(Contd. of page 6) · 14.6 Special precautions for user Not applicable. · 14.7 Maritime transport in bulk according to IMO Not applicable. instruments · UN "Model Regulation": Void

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · National regulations
- Water hazard class: Water hazard class 1 (Self-assessment): slightly hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Alteration in the context will be marked with a cross (*).

· Relevant phrases

- Highly flammable liquid and vapour. H225
- H301 *Toxic if swallowed.*
- H302 Harmful if swallowed.
- H310 Fatal in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H336 May cause drowsiness or dizziness.
- Very toxic to aquatic life. H400
- H410 Very toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Department issuing data specification sheet: Productmanagement.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Acute Tox. 3: Acute toxicity – Category 3

Acute Tox. 4: Acute toxicity - Category 4

(Contd. on page 8)

Page 8/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 01.06.2022

Version number 9 (replaces version 8)

Product name 2K Supra A.T.

(Contd. of page 7)

Revision: 01.06.2022

Acute Tox. 2: Acute toxicity - Category 2

Skin Corr. 1C: Skin corrosion/irritation – Category 1C Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1A: Skin sensitisation – Category 1A STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

* Data compared to the previous version altered.