# pandomo

AN ARDEX BRAND



## Technical Datasheet PANDOMO Care & Clean

### Sustaining Care

- For care and cleaning of oiled PANDOMO<sup>®</sup> floors which have been treated with PANDOMO<sup>®</sup> SP-GS, PANDOMO<sup>®</sup> SP-MS or PANDOMO<sup>®</sup> SP-PS water-based PU sealer
- > Loosens contamination
- > Repairing effect in the protective film
- > Low foam-forming
- > Concentrate
- > Extremely high-yield



#### **Application Areas**

For monthly maintenance care of all PANDOMO® floors which have been treated with PANDOMO® SP-SL stone oil, PANDOMO® Impregnation, PANDOMO® SP-GS, PANDO-MO® SP-MS or PANDOMO® SP-PS water-based PU sealer.

PANDOMO® CARE & CLEAN can also be used for the care and cleaning of painted parquet flooring, wooden floors, CV, PVC, cork, polyolefine, linoleum and rubber surfaces, and is also suitable for treating natural and artificial stone.

For indoors only. Suitable for machine cleaning.

#### **Properties**

- > loosens contamination
- > repairing effect in the protective film
- > low foam-forming

The cleaning components that it contains loosen contamination from the surface and retain them in the mopping water. Small quantities of the care components remain on the surface after drying.

#### Processing

#### A) Maintenance cleaning:

First remove dirt and sand with a brush or the brush side of the vacuum cleaner, since both have a similar effect to sandpaper. Shake container well before use. Dilute PANDOMO $^{\odot}$  CARE & CLEAN (approx. 50 to 100 ml in 10 litres of water, sufficient for approx 100 m<sup>2</sup>).

Wipe the surfaces keeping them damp, and then allow to dry. Do not mop with fresh water.

It is advisable to work with two buckets. One bucket for the clean PANDOMO® CARE & CLEAN mopping water, the other for wringing out the floor cloth.

#### B) Repairing small scratches and the like:

Dilute PANDOMO<sup>®</sup> CARE & CLEAN (approx. 100 ml in 10 litres of water). Mop the floor wet. Small scratches, matt areas and the like disappear or become less visible. After drying, polish away any streaks that occur with a dry cloth or a mop.

#### Important notes

Do not mix PANDOMO<sup>®</sup> CARE & CLEAN with other care and cleaning materials. The drying time is approx. 60 minutes. Do not walk on or mop the floor while the PANDOMO<sup>®</sup> CARE & CLEAN film is still damp. The care film of PANDOMO<sup>®</sup> CARE & CLEAN can be completely removed using PANDOMO<sup>®</sup> CLEANER, see relevant technical data

#### General

The floor must not be soaking wet during cleaning. Always treat the floor in a damp condition only.

#### Safety/disposal instructions:

Keep out of the reach of children. Dispose of contents/ container in accordance with the local / regional / national / international regulations.



# pandomo



AN ARDEX BRAND

## Technical Datasheet PANDOMO Care & Clean

### Sustaining Care

Technical Specifications According to ARDEX Quality Standards:	
Material requirement	approx. 1 – 10 ml/m²
Density	approx. 1.0 g/cm <sup>3</sup>
pH Value	approx. 7.0
Appearance	liquid, clear, colourless
Solubility in water:	completely soluble
Processing temperature:	approx. + 5 – + 25°C
Drying time:	approx. 60 minutes
Marking in accordance with GHS/CLP:	none
Marking in accordance with GGVSEB/ADR:	none
GISCODE	GU 50
Packaging:	Plastic canister containing 2.5 L net Plastic bottle containing 500 ml net
Storage and Shelf Life	Store in a cool but frost-free location, and ensure that the container is properly sealed after opening Can be stored for approx. 36 months in the original sealed container. Use contents of container as soon as possible after opening.

ARDEX Yapı Malzemeleri Limited Şirketi İstanbul Deri Organize Sanayi Bölgesi Desen Sok. No:14/A C1 Özel Parsel Tuzla / İstanbul / Türkiye Tel.: +90 (0) 216 394 0114 Fax: +90 (0) 216 394 0377 info@ardex.com.tr www.ardex.com.tr Manufacturer with ISO 9001/14001 Quality Management System Certificate.

We guarantee the consistent high quality of our products. Our recommendations for use are based on practical trials and experience. However they can only serve as general recommendations and do not constitute a promise of the described properties as we have no control over site conditions or the execution of the work. Country-specific regulations based on local standards, building regulations, codes of practice and industrial guidelines may affect the specific recommendations for processing this product.